

Kerabit 3000 U

Päivitetty 17.5.2024 Tulostettu 21.5.2024

Kerabit 3000 U is an underlay membrane in multi-layer membrane system, glued with molten bitumen.

The carrier consists of polyester. Sand granules on the top both side of the membrane.



Technical data

Manufacturer / Manufactured for	Kerabit Oy, Lohja plant
Country of origin	Finland
Conformity marking	CE mark
Reaction to fire	Manufacturer's fire testing certificate
Fire Classification	B _{ROOF} (t2)
Manufacturer's declaration of conformity	Kerabit modified bitumen roofing materials
Quality control	Quality control agreement between the Plant and Eurofins Expert Services Oy
Nominal thickness	approx. 2,5 mm
Nominal weight	3000 g/m ²
Weight of the supportive layer	170 g/m ² (+/- 10 g/m ²)
Supportive layer	Polyester
Rolls size	1 x 10 m / 10 m ²
Packages / pallet	31 rolls
Weight / package	30 kg
Weight / pallet	955 kg

Additional information

Handling and storage

Modified bitumen membranes are to be stored on pallets in a dry and cool place. Use a plastic hood or tarpaulin for protection. When the outdoor temperature exceeds +40°C, the rolls must be protected from sunlight.

Applications

The product is used as underlay or intermediate layer of multi-layer roofing and water pressure insulation.