

Kerabit 3200 UTL Fleece

Päivitetty 25.4.2023 Tulostettu 20.5.2024

Kerabit 3200 UTL Fleece is a line-torch-on (K-TMS 170/3200 torch-on) underlay membrane of product category 2 for multi-layer roofing. The product also serves as an underlay (AKE and AKK 1) for non-continuous roofing and as a vapour-barrier membrane (BH 1).

The carrier is of polyester. The lower surface of the product is torch-on bitumen and the upper surface is polypropylene non-woven fabric.

The product has been approved for use in buildings with the Nordic Swan Ecolabel.



Technical data

Manufacturer / Manufactured for	Kerabit Oy, Lohja plant
Country of origin	Finland
Conformity marking	CE
Reaction to fire	Manufacturer's declaration of the fire test
Fire Classification	B _{ROOF} (t2)
Manufacturer's declaration of conformity	Kerabit modified bitumen roofing
Quality control	Quality control carried out at the Plant quality control and a quality control agreement between the Plant and Eurofins Expert Services Oy
SFS-labeling	K-TMS 170/3200 torch-on
Product category	TL 2, AKE, AKK 1, BH 1
Nominal thickness	approx. 2,6 mm
Nominal weight	3200 g/m ²
Weight of the supportive layer	170 g/m ² (+/- 5 g/m ²)
Supportive layer	polyester
Surface type	PP non-woven fabric
Rolls size	1 x 10 m / 10 m ²
Packages / pallet	24 rolls
Weight / package	32 kg
Weight / pallet	793 kg

Additional information

Applications

The product is used as an underlay membrane for multi-layer roofing, as an underlay for non-continuous roofing and as a vapour-barrier membrane.

Handling and storage

Modified bitumen membranes are stored on pallets in a dry and cool place in an upright position. The rolls must be protected with plastic hoods or tarps. In temperatures in excess of +40 °C, the rolls must be stored away from sunlight.